




CUSTOMER:	REF NO :CA000104		
DESCRIPTION:	UU16 LINE FILTER	VERSION:A	PAGE:1/2

SPECIFICATION

Compliant RoHS


I .PHYSICAL DIMENSIONS (Unit:mm)

A	B	C	D	L	P1	P2
24.0 max	20.0 max	28.0max	Ø0.7±0.1	4.5±1.0	13.0±0.5	10.0±0.5



BOTTOM VIEW

II . WINDING DIAGRAM



Note: ● Winding start

APP	CHK	DRG

SAMPLE NO.	
MATSUTA NO.	63-161617650Q
SPEC. NO.	TR17650
ISSUE DATE.	2011/06/27

MATSUTA CO.,LTD.

Flat 15, 10/F, Block B, Tonic Industrial Centre,
19 Lam Hing Street, Kowloon Bay, Hong Kong.

Tel: (852) 2796 6693

Fax: (852) 2796 3530, 2754 5674

E-mail: matsuta@matsuta.com.hk

Web site: <http://www.matsuta.com>

CUSTOMER:	REF NO :CA000104		
DESCRIPTION:	UU16 LINE FILTER	VERSION:A	PAGE:2/2

SPECIFICATION

Compliant RoHS

III.ELECTRICAL PERFORMANCE

C.D.	N(Ts) REF	WIRE 2UEW	START	END	INDUCTANCE	DC RESIST
N1	35	Ø0.6mm	1	2	2.5mH min	120mΩ max
N2	35	Ø0.6mm	4	3	2.5mH min	120mΩ max
N O T E	1. Inductance measured by CH-100LCR (at 1KHz/0.25V).					
	2. DC Resist measured by CH-502AC (at 25°C).					
	3. HI-POT test: Coil to Coil 1.2KV/AC/3mA for 2seconds. Coil to Core 1.2KV/AC/3mA for 2seconds.					

IV、 MATERIALS LIST:

NO	ITEM	MATERIALS	MANUFACTURER	UL FILE NO
1	BOBBIN	UU16 PHENOLIC PJ-4	SHANGHAI TWIN-TREE PLASTICS FACTORY	E106276
2	CLIP	UU16	CHUANG SHUN ELECTRONIC	N/A
3	CORE	P7K UU16 JH7A UU16 R7K UU16	PANSCIENCE JPMF DMEGC	N/A
4	WIRE	2UEW 130°C	FENG CHING METAL CORP	E172395
5	VARNISH	1032BOH	QUALIPOLY CHEMICAL CORP	E213437

APP	CHK	DRG	SAMPLE NO.	
			MATSUTA NO.	63-161617650Q
			SPEC. NO.	TR17650
			ISSUE DATE.	2011/06/27